

IN20-ISAS3.0MBFX

iSAS 3mp Mini Bullet Camera



Features:

- 3MP (2048×1536) real time encoding image resolution 2048x1536
- ICR infrared filter for day/night function
- 10-20m night vision range
- Support 3D noise reduction, digital WDR
- Support ROI
- Support POE
- Support smart phone, pad, remote surveillance
- Support P2P

Camera	
Image sensor	1/3"CMOS
Image pixels	2048x1536
Electronic shutter	1/25s~ 1/100000s
Iris Type	Fixed Iris
Min. illumination	0lux (IR ON)
Lens	3.6mm (6mm、 8mm options)
Mount type	M12
Day/Night mode	ICR infrared filter
WDR	WDR
Noise Reduction	2D/3DNR
Image	
Compression	H.264 / MJPEG
H.264 standard	Baseline Profile / Main Profile / High Profile
Encode	VBR/CBR
Quality	VBR 5 level , CBR no limit
Bit rate:	64Kbps ~ 8Mbps
Resolution:	3MP (2048×1536) 、 1080P (1920×1080) 、 720P (1280×720) 、 D1、 CIF、 480x240
Frame rate:	3MP (1~15fps) / 1920x1080 (1~30fps)
	1280x720 (1~10fps) / D1 (1~30fps) / CIF (1~30fps)
	CIF (1~30fps) / 480x240 (1~30fps)
Image config.	ROI, Brightness, Chroma, Saturation, Contrast, WDR, Sharpness, Noise Reduction (Via IE & client end)
Audio compression	G711A/U
ROI	Support ROI Configuration for each stream independently.
Interface	
Internet	RJ45
Video out	NO
Audio	NO
Storage	NO
RS485	NO
Alarm in	NO
Alarm out	NO
Function	
Remote surveillance	IE browser, CMS remote control
Online user	10 users, support multi-stream real time transmission.
Network protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Interface protocol	ONVIF、 GB-T/28181-2011
Storage	Remote storage
Smart alarm	Motion detection
PTZ	NO
PoE	Support
Night vision range	10-20m
Water proof	IP66
Others	
Power supply	DC12V/PoE
Power consumption	Max. 4W
Working environment	-20℃ ~ 50℃ , 10% ~ 90% humidity
Dimension	Φ64mm×183mm
Weight(net)	412g