

Validation Solution

The simple and easy printer to issue barcode discount vouchers



valiprint



Validation Solution

The simple and easy printer to issue barcode discount vouchers

BASE MODEL

Desk-top or handheld validation/discount voucher printer

1 button for 1 validation type

Stand-alone

Battery operation (includes charger power supply)

OPTIONS

4 discounts from one ValiPrint
– applicable to different types of validation such as money value, time, percentage or different rate

The ValiPrint is available in single or 4 validation/discount versions. It is simple and easy to issue a barcode discount voucher with the ValiPrint. The flexible, light and portable voucher printer is ergonomically styled for retail environments. Each voucher is printed with an encrypted barcode and unique number which avoids fraudulent use of the validation. This low cost, stand-alone receipt printer is fully auditable and can be combined with other validation types of the ZEAG product range. A typical application would be in retail stores that offer discounted parking fees to customers that buy goods from the store. The voucher is printed by the shop staff and handed to the customer. Payment or exit stations will then scan the barcode and re-calculate the fee with the predetermined validation/discount. Multiple discount vouchers can be used.

STANDARD FEATURES

- Voucher is thermal printed using a low cost receipt paper
- Fully auditable – shift report available detailing the number of validations issued
- Unique number for each voucher
- Encrypted barcode to avoid fraudulent validation
- Barcode scanner required at Payment Station, Fee Computer or Exit Stations
- Validation types can be combined in same car park with other ZEAG product range validation solutions

Dimensions

- Width: 85mm / 3.3"
- Height: 55mm / 2.2"
- Depth: 150mm / 5.9"
- Weight: approx. 450 g / 1 lbs (including paper and power supply)

Power

- Recharger power supply: 100 to 240 VAC
- NIMH (Nickel Metal Hydride) AA format rechargeable battery

Environment

- Ambient temperature: 0°C / 32 F to +40°C / 104 F (in covered/ protected environment)

