

The fixed **275/M30FB 1200F** PILOMAT have been designed and built with architectural appearance similar to that of the mobile PILOMAT and therefore also allows the combined use of both versions. The current models are the result of the development of more than 15 years of experience.


**GENERAL FEATURES**

The fixed antiterrorism PILOMAT are used to separate and prevent vehicles from breaching the perimeter of the following areas: Research Centres Embassies, Police Headquarters, Military Bases, Ministerial Buildings Sites in Sensitive Areas.

- **MFB SERIES:** these items are designed to ensure antiterrorism defence, and must be cemented into the ground at a depth that meets the standards of resistance of breakout.
- **Choice of optional configurations:**
  - FE370 or AISI 304 stainless steel moving cylinders
  - custom colours
  - flashing lights integrated in the head.

FIXED CYLINDER	FE 510 STEEL (IRON)
FIXED CYLINDER NOMINAL DIAMETER	275 mm
FIXED CYLINDER HEIGHT	1200 mm
FIXED CYLINDER FE 510 STEEL THICKNESS	15 mm
FIXED CYLINDER FE 510 STEEL FINISH	POLYESTER POWDER PAINT - STANDARD GREY ANTHRACITE
OTHER FIXED CYLINDER FINISH	RIBS ON CYLINDERS SURFACE - 316 AISI STAINLESS STEEL BRUSHED COVERING 1,5 mm
REFLECTING ADHESIVE STRIP	YES - HEIGHT 55 mm
IMPACT RESISTANCE (WITHOUT DEFORMATION)	700.000 J
BREAKOUT RESISTANCE	1.200.000 J



■ BREAKOUT RESISTANCE 1.200.000 J  
 □ IMPACT RESISTANCE 700.000 J



**MAIN DIMENSIONS**

