PILSMAT

PILOMAT 127/PF 600F

FIXED PILOMAT

The fixed 127/PF 600F PILOMAT have been designed and built with architectural appearence similar to that of the mobile PILOMAT and therefore also allows the combined use of both versions. The current models are the result of the development of more than 15 years of experience.



GENERAL FEATURES

The fixed PILOMAT are used in public or private areas in order to define or prevent the parking of vehicles, for preventing access to vehicles in pedestrian areas.

- **PF SERIES:** These items can be cemented to the ground (in this case, the resistance to breakage depends on the depth to which it is anchored into the ground) or be secured in place by chemical anchors in places where you cannot make the same anchor, or where masonry is already completed.

- Choice of optional configurations:

- FE370 or AISI 304 stainless steel moving cylinders
- custom colours
- flashing lights integrated in the head.

| FIXED CYLINDER | FE 370 STEEL (IRON) – AISI 304 / 316 STAINLESS STEEL |
|--|--|
| FIXED CYLINDER NOMINAL DIAMETER | 127 mm |
| FIXED CYLINDER HEIGHT | 600 mm |
| FIXED CYLINDER FE 370 STEEL THICKNESS | 6 mm |
| FIXED CYLINDER STAINLESS STEEL THICKNESS | 6 mm |
| FIXED CYLINDER FE 370 STEEL FINISH | POLYESTER POWDER PAINT - STANDARD GREY ANTHRACITE |
| FIXED CYLINDER STAINLESS STEEL FINISH | POLYESTER POWDER PAINT - STANDARD GREY ANTHRACITE OR BRUSHED |
| REFLECTING ADHESIVE STRIP | YES - HEIGHT 23 mm |
| IMPACT RESISTANCE (WITHOUT DEFORMATION) | 30.000 J |
| BREAKOUT RESISTANCE | 150.000 J |