

The fixed **127/PL 600F** PILOMAT have been designed and built with architectural appearance similar to that of the mobile PILOMAT and therefore also allows the combined use of both versions. The current models are the result of the development of more than 15 years of experience.

**GENERAL FEATURES**


The fixed PILOMAT are used in public or private areas in order to define or prevent the parking of vehicles, for preventing access to vehicles in pedestrian areas.

- **PL SERIES:** These items, with a counterframe to wall, in addition to the architectural appearance of the automatic PILOMAT, allow the removal of the bollard in the event of such a removal being needed, or if impact has occurred.

- **Choice of optional configurations:**

- FE370 or AISI 304 stainless steel moving cylinders
- custom colours
- flashing lights integrated in the head.

FIXED CYLINDER	FE 370 STEEL (IRON) – AISI 304 / 316 STAINLESS STEEL
FIXED CYLINDER NOMINAL DIAMETER	127 mm
FIXED CYLINDER HEIGHT	600 mm
FIXED CYLINDER FE 370 STEEL THICKNESS	6 mm
FIXED CYLINDER STAINLESS STEEL THICKNESS	6 mm
FIXED CYLINDER FE 370 STEEL FINISH	POLYESTER POWDER PAINT - STANDARD GREY ANTHRACITE
FIXED CYLINDER STAINLESS STEEL FINISH	POLYESTER POWDER PAINT - STANDARD GREY ANTHRACITE OR BRUSHED
REFLECTING ADHESIVE STRIP	YES - HEIGHT 23 mm
IMPACT RESISTANCE (WITHOUT DEFORMATION)	30.000 J
BREAKOUT RESISTANCE	150.000 J