

The fixed **275/PL 800F** PILOMAT have been designed and built with architectural appearance similar to that of the mobile PILOMAT and therefore also allows the combined use of both versions. The current models are the result of the development of more than 15 years of experience.

GENERAL FEATURES

The fixed PILOMAT are used in public or private areas in order to define or prevent the parking of vehicles, for preventing access to vehicles in pedestrian areas.

- **PL SERIES:** These items, with a counterframe to wall, in addition to the architectural appearance of the automatic PILOMAT, allow the removal of the bollard in the event of such a removal being needed, or if impact has occurred.

- **Choice of optional configurations:**

- FE370 or AISI 304 stainless steel moving cylinders
- custom colours
- flashing lights integrated in the head.



| | |
|--|--|
| FIXED CYLINDER | FE 370 STEEL (IRON) – AISI 304 / 316 STAINLESS STEEL |
| FIXED CYLINDER NOMINAL DIAMETER | 275 mm |
| FIXED CYLINDER HEIGHT | 800 mm |
| FIXED CYLINDER FE 370 STEEL THICKNESS | 6 mm |
| FIXED CYLINDER STAINLESS STEEL THICKNESS | 6 mm |
| FIXED CYLINDER FE 370 STEEL FINISH | POLYESTER POWDER PAINT - STANDARD GREY ANTHRACITE |
| FIXED CYLINDER STAINLESS STEEL FINISH | POLYESTER POWDER PAINT - STANDARD GREY ANTHRACITE OR BRUSHED |
| REFLECTING ADHESIVE STRIP | YES - HEIGHT 55 mm |
| IMPACT RESISTANCE (WITHOUT DEFORMATION) | 40.000 J |
| BREAKOUT RESISTANCE | 250.000 J |